

With the simplest configuration and user interface available in the market Bpos is the perfect solution for large scale and affordable implementation of electronic products distribution.

Low cost, durable & ergonomic the Bpos is a powerful communication device which allows online and interactive customer management.

Its powerful technology combines standard cell phone functions, like phone calls and SMS, basic POS functions and micro browser GPRS application for fast deployment of new products and transactions.



The Bpos



Processor	ARM 9
Memory	128 Mb Flash
Communication	GSM Quad band (850/900/1800/1900)
GSM Antenna	SMA connector 50 Ω impedance, 3dB Gain
Keyboard	24 keys, 4 navigation keys, 5 function keys
Display	128*64 LCD Backlight
Thermal printer	Speed : 60mm/sec Easy loading with paper detection Resolution : 8dot/mm
Peripheral port	RS232 (RJ 12 connector)
Size (in mm)	Terminal : 155x235x95 Paper roll : 58/ø50
Weight (in gr)	750 (without battery)
Environment	Working Temperature : -10°C / +55°C Storage temperature : -40°C / +90°C Humidity : < 95% @ 40°C
Material	ABS (Acrylonitrile Butadiene Styrene)
Power supply	Input : AC 110-240 V - 50Hz (max 300mA) Output : 12 VDC (max 2A)
Power switch	Rocker switch
Ring Volume	Adjustable
Battery	Ni-MH 3.6V – 1200 mA Charging time : 8 hr Standby time : 48 hr

THE BPOS



WWW.THEBPOSONLINE.COM

Make and receive phone calls, send and receive SMS, use existing USSD services, print your vouchers and manage your own transactional GPRS application using embedded micro browser.

